

MOBIREX MR 130(i) PRO



Focus on power



The MR 130(i) PRO impact crusher covers a very wide application range in natural stone and recycling. With its heavy rotor and powerful electric 250 kW drive, the crushing unit guarantees very high and stable throughput. Continuous crusher utilisation is ensured thanks to the Continuous Feed System (CFS).

Precision in the foreground



Top product quality is expected from an impact crusher - and this is what the MR 130(i) PRO delivers together with a high production capacity.

Thanks to the optional double-deck post screening unit, splitting of the target grain size into two separate material flows is possible. Lightweight material can also be removed from both material flows by wind sifters. Users can count on excellent final product quality

An eye on sustainability



Sustainable solutions ensure real future security.

Thanks to its E-DRIVE all-electric drive concept, the MR 130(i) PRO excels with the option of external power supply. The CO₂-free operation guarantees low energy consumption per ton of final product.

If the plant is operated via the diesel generator, the **power- and load-dependent fan** ensures noise reduction and improved economy.

MOBIREX MR 130(i) PRO

1 Feeding unit

- > Generously dimensioned basic hopper
- > Hydraulically foldable and lockable - for quicker set-up from the ground via radio remote control
- > Hopper extension⁺ increases the feed volume and ensures a continuous feed
- > Hopper filling aid⁺ for feeding via wheel loader from behind, filling width approx. 3.30 m

2 Prescreen

- > Independently vibrating prescreen for effective screening of fines
- > Co-vibrating bypass flap⁺ for fast change-over of the material flow of the prescreen material without installation of a dummy cover in the lower deck
- > Optimised screen surfaces (increased screening surface with slotted grate) ensure a higher screening performance and reduced cleaning requirements
- > Side discharge conveyor⁺ can be used on both sides, rigid or hydraulically foldable

3 Continuous Feed System (CFS)

- > Continuous crusher load through the intelligent CFS feed control:
 - > Measurement of crusher load and engine load
 - > Vibrating feeder and prescreen are controlled according to the load status
 - > After an overload, material transport is continued immediately
- > Fewer interruptions to production - up 10 % more daily output
- > Less burden is placed on the downstream components, wear is also reduced and the share of oversize grain is also minimised

4 Crusher unit

- > Powerful electric (250 kW) crusher drive
 - > High continuous throughput of the impact crusher for a wide range of applications in natural stone and recycling
- Fully hydraulic gap adjustment and overload system**
- > Automatic zero-point determination for precise gap setting via touch panel
 - > The effective overload function opens the lower impact toggle in the event of uncrushable elements and then moves back automatically to the preset position
 - > In the event that uncrushable components are too large, a pressure plate is provided as a last resort to protect the crusher

5 SPECTIVE control system

- > **SPECTIVE touch panel:** all components and function can be controlled via touch panel
- > **SPECTIVE CONNECT⁺:** all important information can be directly accessed on a smartphone; higher productivity as a result of fewer interruptions to the production process
- > **SPECTIVE radio remote control:** for operating all important components from a safe distance, ensuring increased work safety
- > **SPECTIVE radio remote control, small⁺:** the most important operating functions are conveniently combined, minimum space requirements in the operator cabin



- > **Quick Track⁺:** for fast and simple movement of the machine while it is operational - allows work to be completed faster since the system does not need to be shut down when it is moved; conveniently operated via radio remote control
- > **Camera system⁺:** convenient monitoring of the material flow, remote monitor in the excavator, additional connection to SPECTIVE CONNECT
- > **Line coupling⁺:** process coupling for control of the production output; safety coupling for safe interlinking of plants in the line train
- > **Belt scale⁺:** for all relevant conveyors for determining production data



KLEEMANN SUSTAINABILITY describes innovative technologies and solutions which are consistent with the sustainability objectives of the WIRTGEN GROUP.

6 Drive

- > E-DRIVE diesel-electric drive, all drives are electric with the exception of the traction drive and auxiliary functions
- > Local emission-free operation possible through external power supply⁺ (transportable, depending on the country) for increased sustainability
- > Power-dependent fan for lower noise emissions and reduced consumption
- > Ease of physical and visual access to all components relevant to maintenance
- > Raised air intake⁺ for longer filter service lives

7 Magnetic separator

- > Efficient permanent⁺ or electromagnetic⁺ for increased final product quality
- > Can be flexibly attached on chains and individually adjusted in transverse and longitudinal inclination
- > Can be hydraulically raised and lowered for quick response to material congestion
- > Sliding bars in the area below the magnet prevent the crusher discharge conveyor from being pierced by jammed metal parts

8 Post screening unit

- > Large double-deck post screening unit⁺
 - > 8.4 m² screening surface upper deck, 7.2 m² screening surface lower deck
 - > For use as a single-deck or double-deck screen
 - > For producing two classified final grain sizes
- > Wide oversize grain returning system ensures better material flow in the event of a high proportion of light-weight material
- > Medium grain conveyor can be reversed, discharge onto stockpile or oversize grain return conveyor, high production output even when fine feed material is used
- > Two wind sifters⁺ for effective cleaning of the oversize grain and medium grain, resulting in improved final product quality

9 Safety and ergonomics

- > Quick and convenient servicing thanks to easy physical and visual access to all components
- > The "Lock & Turn" rotor safety system ensures maximum operating safety when changing rotor ledges and removing material blockages
- > LED lighting included in basic plant; Premium lighting⁺ for extended illumination of work areas
- > Central drain point for fluids for ergonomic maintenance
- > Lower ground pressure thanks to wide crawler carrier chains, flexible use on poorly prepared ground

10 Environment

- > Thanks to the electric drive, hydraulic oil is only required for setting and set-up functions, which reduces the environmental risk and maintenance costs
- > Reduction of dust to protect the operator and the environment
 - > Spray system at all relevant points, can be cut in and out individually
 - > Belt covers⁺ for rigid side discharge conveyor, fine grain discharge conveyor and crusher discharge conveyor
- > Solutions for noise reduction⁺: insulation of the noise sources by an ergonomic power pack housing, reduction of noise by sealing the open power pack base

TECHNICAL INFORMATION		MR 130(i) PRO
Feed capacity up to approx. (t/h)		600
Max. feed size (mm)		1,040 x 650
Hopper volume (with extension) (m ³)		5 (9)
Drive concept		diesel-electric
Diesel engine drive power (kW)		478
Transport height (mm)		3,900
Transport length (with post screening unit) (mm)		21,000 (23,200)
Transport width (mm)		3,500
Transport weight post screening unit (kg)		12,000
Transport weight of basic plant - max. configuration (kg)		64,000 - 83,000

© KLEEMANN GmbH 3078688 Subject to change at any time. Version: 06/22-V1

